




Circular Linear Light



OZ-CL6060



Basic Information

Product Name	Circular Linear	Body Material	Aluminum + Pc
Model	OZ-CL6060	Working Temperature	-0°C ~ 50°C
Protection Level	Class I	Installation	Ceiling, Suspended
Ingress Protection	IP 20	Shell Cover	White / Black
Usage	Indoor		


Physical Parameter

Optical Parameter

Input Voltage	100V-277V / 200-240V
Color Temperature	3000K, 4000K, 6000K
Life Span	50,000 hrs.
UGR	<19


Additional Features

Sensor	Optional
Emergency	Optional
Dimming	Optional



Item Ref	Power	Source	Light Efficiency	P.F	CRI	Product Size D*W*H -mm
OZ-CL6060-45	15 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ450*60*60mm
OZ-CL6060-60	30 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ600*60*60mm
OZ-CL6060-90	40 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ900*60*60mm
OZ-CL6060-100	40 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ1000*60*60mm
OZ-CL6060-120	40 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ1200*60*60mm
OZ-CL6060-150	80 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ1500*60*60mm
OZ-CL6060-180	120 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ1800*60*60mm
OZ-CL6060-200	130 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ2000*60*60mm
OZ-CL6060-2400	150 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ2400*60*60mm
OZ-CL6060-300	180 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ3000*60*60mm
OZ-CL6060-400	280 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ4000*60*60mm
OZ-CL6060-500	320 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ5000*60*60mm

OZ-CL6080



Basic Information

Product Name	Circular Linear	Body Material	Aluminum + Pc
Model	OZ-CL6080	Working Temperature	-0°C ~ 50°C
Protection Level	Class I	Installation	Ceiling, Suspended
Ingress Protection	IP 20	Shell Cover	White / Black
Usage	Indoor		

Physical Parameter

Optical Parameter

Input Voltage	100V-277V / 200-240V
Color Temperature	3000K, 4000K, 6000K
Life Span	50,000 hrs.
UGR	<19

Additional Features

Sensor	Optional
Emergency	Optional
Dimming	Optional



Item Ref	Power	Source	Light Efficiency	P.F	CRI	Product Size D*W*H -mm
OZ-CL6080-45	15 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ450*60*80mm
OZ-CL6080-60	30 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ600*60*80mm
OZ-CL6080-90	40 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ900*60*80mm
OZ-CL6080100	40 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ1000*60*80mm
OZ-CL6080-120	40 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ1200*60*80mm
OZ-CL6080-150	80 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ1500*60*80mm
OZ-CL6080-180	120 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ1800*60*80mm
OZ-CL6080-200	130 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ2000*60*80mm
OZ-CL6080-240	150 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ2400*60*80mm
OZ-CL6080-300	180 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ3000*60*80mm
OZ-CL6080-400	280 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ4000*60*80mm
OZ-CL6080-500	320 watt	SMD2835	105 lm/w	> 0.95	> 80	Φ5000*60*80mm