

**LED HIGHBAY LIGHT**





## OHC-02

### Basic Information

Product Name	Led Highbay Classic
Model	OHC-02 – Classic
Protection Level	Class I , IK08
Ingress Protection	IP 66
Usage	Commercial, Industrial,

### Physical Parameter


Material	Aluminum Die-cast
Heatsink	Aluminum 6063
Working Temperature	-20 ~ +50
Installation	Ceiling, Suspended
Reflector	45°/90°/120°

### Optical Parameter

Input Voltage	90-305 Volt
Color Temperature	3000K, 4000K, 6000K
Life Span	50,000 hrs.
Driver	Meanwell – External Driver Box
Led-SMD	Lumileds - Philips

### Additional Features

Sensor	(S) - Optional
Emergency	(EM) - Optional
Dimmable	(D) - Optional
Standard	EN60598-1
Lumens * Optional	110Lm, 120Lm, 130Lm / watt



Item Ref	Power	Source	P.F	CRI	Product Size D x H mm
OHC-02-100	100 watt	SMD 3030	≥ 0.9	> 80	200x80
OHC-02-150	150 watt	SMD 3030	≥ 0.9	> 80	200x120
OHC-02-200	200 watt	SMD 3030	≥ 0.9	> 80	260x100
OHC-02-250	250 watt	SMD 3030	≥ 0.9	> 80	260x120
OHC-02-300	300 watt	SMD 3030	≥ 0.9	> 80	260x180
OHC-02-370	400 watt	SMD 3030	≥ 0.9	> 80	260x200
OHC-02-500	500 watt	SMD 3030	≥ 0.9	> 80	280x200

\* OHC-02-500 – Glass clipped on reflector

