

OZ-06P



Basic Information


Product Name	Water Proof	Body Material	Polycarbonate
Model	OZ-06P	Working Temperature	-20 ~ 40
Protection Level	Class II	Installation	Ceiling, Suspended
Ingress Protection	IP 65		
Usage	Intensive, Dusty, Rain		

Physical Parameter

Optical Parameter

Input Voltage	220-240V	Sensor	No
Color Temperature	3000K, 4000K, 6000K	Emergency	No
Life Span	50,000 hrs.	Through Wiring	Optional

Additional Features



Item Ref	Power	Source	Lumen	Light Efficiency	P.F	CRI	Product Size L*W*H
OZ-06P-0610	10 watt	SMD2835	900 lm	90 lm/w	> 0.9	> 80	700*50*35
OZ-06P-0618	18 watt	SMD2835	1600 lm	90 lm/w	> 0.9	> 80	700*50*35
OZ-06P-1218	18 watt	SMD2835	1600 lm	90 lm/w	> 0.9	> 80	1230*53*35
OZ-06P-1236	36 watt	SMD2835	3500 lm	97 lm/w	> 0.9	> 80	1230*53*35
OZ-06P-1524	24 watt	SMD2835	2160 lm	90 lm/w	> 0.9	> 80	1510*53*35
OZ-06P-1545	45 watt	SMD2835	4300 lm	96 lm/w	> 0.9	> 80	1510*53*35

- New Fashionable Extruded Type
- Instant wiring coupler optional
- Serial connection optional